

Xstream

Making parcel automation
faster and more efficient

Learn more:
888-821-SORT (7678)
www.npisorters.com

The perfect solution for:

- Postal Organizations
- Couriers
- Logistics
- Magazine Publishers
- Distribution
- Fulfillment
- Warehouse Distribution

*Throughput up to 30,000
parcels and flats per hour
in a small footprint*



Xstream

FEATURES AND BENEFITS

- Compact and scalable design
- Inbound and Outbound package processing
- Multi-sided omni-directional barcode reading capability for most 1D, 2D and Postal barcode types
- Sorts plastic, poly wrap, boxes, flats and most irregular pieces
- Handles a wide variety of product sizes, shapes and weights
- Integrates with existing conveyor systems
- Multiple product and output options
- Versatile and user-friendly Windows-based user interface

PACKAGE TYPES

BOXES



POLY BAGS



FLATS



OUTPUT OPTIONS

COLLAPSIBLE STORAGE BINS



MAIL / PARCEL TRUCKS



PALLET BOXES



POWER REQUIREMENTS

VOLTAGE	480 VAC 3 Phase / 415 VAC 3 Phase, Wye Configuration
FREQUENCY	60 Hz / 50 Hz

EQUIPMENT Semi-Automated Parcel Infeed

GAPPER MODULE	Creates consistent gap between packages
READER RAMP MODULE	- Elevates packages to output level - Mounting provision for top and bottom side cameras
MAX SORTING RATE	Up to 30,000 packages per hour
OUTPUT MODULE	A maximum of 12 outputs per module with options to support almost any type of output storage including but not limited to carts, gondolas and gaylords

PHYSICAL MAIL CHARACTERISTICS

LENGTH	Min	4"	[101 mm]
	Max	24"	[610 mm]
WIDTH	Min	4"	[101 mm]
	Max	20"	[508 mm] **
HEIGHT	Min	0.118"	[3 mm]
	Max	18"	[457 mm] **
WEIGHT	Min	0.8 oz	[23 g]
	Max	50 lbs	[22.7 kg] **

** = greater capacity optional



Visit our website
to learn more



NPI

WWW.NPISORTERS.COM

1-888-821-SORT

14901 Trinity Blvd.
Fort Worth, TX 76155